

INDEX TO PARTS I AND II OF THE MOUNTAIN RISK ENGINEERING HANDBOOK

This topic index is meant to be a guide to topics of interest falling within the main section headings. For the reader's convenience, the index has been arranged chapterwise.

CHAPTER 1

| | Page |
|--|------|
| E | |
| engineering | |
| - approaches based on | 1 |
| F | |
| field-based | 5 |
| - practical training using application guide | |
| M | |
| mountain risk engineering handbook | 1 |
| - contents of | 1 |
| - definition of | 3 |
| - evolution of | 1 |
| - purpose of | 2 |
| - structure of | 4 |
| - use of | 4 |
| T | |
| training curriculum | 5,6 |
| - equipment & trainers required for | 6 |

CHAPTER 2

| | |
|----------------|-------|
| A | |
| ablation | 22 |
| accumulation | 18,19 |
| alluvial | 28 |
| - fan or delta | 30 |

| | |
|----------------------------|--------|
| alluvium | 19, 28 |
| aquifer | 24 |
| athensphere | 11 |
| B | |
| bar of river | 19 |
| bed load | 18 |
| C | |
| channels | |
| - braided | 19 |
| - meandering | 19 |
| - straight | 19 |
| channel pattern | 19 |
| channel pool | 19 |
| colluvium | 31 |
| D | |
| depth of compensation | 9 |
| diagenesis | 15 |
| E | |
| earth | 8 |
| - crust shape of | 9 |
| - zones of | 8 |
| eluvial soils or regoliths | 30 |

| | | | |
|--------------------------|----|-----------------------------------|----|
| endogenous | | isostasy | 9 |
| - processes | 15 | isostatic equilibrium | 9 |
| erosion | | L | |
| - bottom | 18 | lithosphere | 9 |
| - lateral | 18 | M | |
| - river | 18 | magma | 15 |
| - sheet | 26 | - crystallisation of | 15 |
| - vertical | 19 | magnetic reversals | 11 |
| erratic, an | 22 | matrix | |
| exfoliation | 16 | - soil | 30 |
| exogenous processes | 14 | Moho Discontinuity | 8 |
| F | | moraines | 31 |
| food plain | 19 | - end | 22 |
| "fossil watches" | 13 | - glacial | 22 |
| G | | - ground | 22 |
| geological processes | 7 | - lateral | |
| geological time scale | 13 | N | |
| geology | 7 | natural levée | 19 |
| - branches of | 7 | O | |
| glaciers | 22 | overland flow | 26 |
| - deposits of | 22 | P | |
| - geological activity of | 22 | particles | 18 |
| - types of | 22 | - transport of | 18 |
| gullying | 26 | percolation | 26 |
| H | | permeabilities | 26 |
| Himalaya | | - variance in multi-layered soils | 26 |
| - young mountain chain | 9 | permeability | 24 |
| hydrogeology | 22 | plate tectonics | 11 |
| hygroscopic water | 24 | porosity | 24 |
| I | | pressure wave | 26 |
| infiltration | 26 | | |
| - factors controlling | 26 | | |

| | |
|--------------------------------|--------|
| R | |
| radioactivity | 13 |
| - discovery of | 13 |
| regoliths | 30 |
| rocks | |
| - intrusive igneous | 15 |
| - metamorphic | 15 |
| - reservoir properties of | 24 |
| - sedimentary | 24 |
| - volcanic igneous | 15 |
| rilling | 26 |
| rivers | |
| - geological action of | 18 |
| - geomorphological features of | 19 |
| S | |
| sediment load | 18 |
| seepage | 25 |
| soil | 28 |
| - alluvial | 28 |
| - eluvial | 30 |
| - origin & description | 28 |
| spring | 25 |
| subduction | 11 |
| suspended load | 18 |
| T | |
| thalweg | 19 |
| till | 22 |
| W | |
| water | 22 |
| - types in rocks | 24 |
| water table | 24 |
| weathering | 15 |
| - chemical | 15, 16 |
| - physical | 16 |

| | |
|------------------|----|
| wetting front | 26 |
| Z | |
| zone of aeration | 24 |
| zones | |
| - earth's inner | 8 |
| - earth's outer | 8 |

CHAPTER 3

| | |
|------------------------------------|--------|
| A | |
| augens | 47 |
| B | |
| batholiths | 40 |
| C | |
| cementation | 50 |
| chemical rocks | 50 |
| classification | |
| - of igneous rocks (felsic, matic) | 43 |
| clastic rocks | 50 |
| cleavage minerals | 34 |
| - colour of | 33 |
| compaction | 50 |
| conchoidal rocks | 34 |
| crystal size | 44, 47 |
| D | |
| deposition | 50 |
| detrital material | 50 |
| dyke swarms | 41 |
| dykes | 41, 51 |

| | | | | | |
|----------------------------|--|--------|--|-----------------------|----|
| E | | | | P | |
| engineering considerations | | 41, 43 | | petrology | 40 |
| even rocks | | 34 | | phyllite | 46 |
| F | | | | porphyroblasts | 47 |
| facies | | 48 | | pyroclastic rocks | 41 |
| foliation | | 47 | | R | |
| form of rocks | | 33 | | rocks | 33 |
| fracture of rocks | | 34 | | - properties of | 33 |
| G | | | | rocks | |
| gneisses | | 46 | | - chemical | 50 |
| granitisation | | 41 | | - detrital or clastic | 50 |
| H | | | | - effusive | 40 |
| hardness of rocks | | 34 | | - extrusive | 40 |
| hackly rocks | | 34 | | - hornfels | 40 |
| L | | | | - hypabyssal | 47 |
| limestone | | 50 | | - igneous | 40 |
| lineation | | 47 | | - intrusive | 50 |
| lithification | | 51 | | - metamorphic | 50 |
| lustre of rocks | | 34 | | - organic | 50 |
| M | | | | - plutonic | 40 |
| metamorphism | | 44 | | - sedimentary | 50 |
| - cataclastic | | 47 | | - volcanic | 40 |
| - classification | | 47 | | S | |
| - regional | | 46 | | sandstone | 50 |
| - types of | | 47 | | schists | 46 |
| migmatite | | 47 | | sectile (minerals) | 35 |
| minerals, composition of | | 33-39 | | sedimentary rocks | 50 |
| Moh's Scale | | 34 | | - formation of | 50 |
| mylonite zones | | 47 | | shale | 50 |
| | | | | specific gravity | 35 |
| | | | | stocks | 40 |
| | | | | streak of minerals | 34 |
| | | | | T | |
| | | | | tenacity | 35 |

| | |
|---------------------|----|
| texture | 46 |
| U | |
| uneven type of rock | 34 |
| V | |
| vesicles | 42 |
| X | |
| xenoliths | 41 |

CHAPTER 4

| | |
|-------------|----|
| A | |
| antiforms | 58 |
| anticline | 58 |
| azimuth | 53 |
| B | |
| bedding | 53 |
| boudinage | 53 |
| breccia | 63 |
| C | |
| cataclasite | 63 |
| cleavage | 58 |
| D | |
| dip | 53 |
| dip | |
| - apparent | 53 |
| - direction | 53 |

| | |
|------------------|----|
| F | |
| faulting | 59 |
| faults | |
| - dip | 59 |
| - dip-slip | 59 |
| - normal | 59 |
| - oblique - slip | 59 |
| - reverse | 59 |
| - slip | 59 |
| - strike | 59 |
| - strike-slip | 59 |
| - thrust | 59 |

| | |
|---------------|--------|
| fractures | 59 |
| folds | |
| - asymmetric | 58 |
| - close | 58 |
| - gentle | 58 |
| - geometry of | 58 |
| - inclined | 58 |
| - isoclinal | 58 |
| - open | 58 |
| - parallel | 58 |
| - parts of | 58 |
| - recumbent | 58 |
| - similar | 58 |
| - single | 57, 58 |
| - symmetric | 58 |
| - tight | 58 |
| - parts of | 57 |
| - hinge lines | 57 |
| - axial plane | 57 |
| - crest | 57 |

| | |
|----------|----|
| G | |
| gouge | 63 |

| | |
|--------------|----|
| H | |
| hanging wall | 59 |

| | |
|-------------|----|
| I | |
| imbrication | 59 |

J

| | |
|---------------------------|----|
| joints | 63 |
| joints | |
| - columnar | 63 |
| - conjugate | 63 |
| - dip | 63 |
| - longitudinal or tension | 63 |
| - transverse or slip | 63 |

M

| | |
|----------|----|
| mylonite | 63 |
|----------|----|

N

| | |
|-------|----|
| nappe | 59 |
|-------|----|

P

| | |
|--------|----|
| plunge | 53 |
|--------|----|

S

| | |
|----------------------|----|
| secondary structures | 53 |
|----------------------|----|

| | |
|--------------|----|
| slickensides | 63 |
|--------------|----|

| | |
|------------------------|----|
| small-scale structures | 58 |
|------------------------|----|

| | |
|--------|----|
| strike | 53 |
|--------|----|

| | |
|--------------------|----|
| structural geology | 53 |
|--------------------|----|

| | |
|------------|--|
| structures | |
|------------|--|

| | |
|-----------|----|
| - primary | 53 |
|-----------|----|

| | |
|-------------------------|----|
| - secondary or tectonic | 53 |
|-------------------------|----|

| | |
|----------|----|
| syncline | 58 |
|----------|----|

| | |
|----------|----|
| synforms | 58 |
|----------|----|

T

| | |
|-------|----|
| trend | 53 |
|-------|----|

CHAPTER 5**A**

| | |
|-------------------------------------|----|
| alternation, phyllite and quartzite | 67 |
|-------------------------------------|----|

C

| | |
|----------------------|----|
| central crystallines | 68 |
|----------------------|----|

| | |
|-----------------------------|--------|
| colluvium, deeply weathered | 66, 67 |
|-----------------------------|--------|

D

| | |
|----------------------------------|----|
| dolomite, medium to thick-bedded | 66 |
|----------------------------------|----|

G

| | |
|----------------|----|
| Gangetic plain | 64 |
|----------------|----|

H

| | |
|-----------------|----|
| <i>Himalaya</i> | 64 |
|-----------------|----|

| | |
|----------|----|
| - higher | 68 |
|----------|----|

| | |
|----------|--------|
| - lesser | 64, 65 |
|----------|--------|

| | |
|------------------|--------|
| - tectonic zones | 64, 65 |
|------------------|--------|

I

| | |
|-------------------------------|----|
| interbedded quartzite + shale | 66 |
|-------------------------------|----|

K

| | |
|---------|----|
| Klippen | 67 |
|---------|----|

M

| | |
|---------------------------|----|
| Main Frontal Thrust (MFT) | 64 |
|---------------------------|----|

| | |
|----------------------------|----|
| Main Boundary Thrust (MBT) | 65 |
|----------------------------|----|

| | |
|------------------|--------|
| metamorphic belt | 67, 68 |
|------------------|--------|

S

| | |
|------------------|-------|
| sedimentary belt | 65-67 |
|------------------|-------|

| | |
|----------|--------|
| Siwaliks | 64, 65 |
|----------|--------|

| | |
|-----------------------------------|----|
| slate, very fractured and crumbly | 66 |
|-----------------------------------|----|

| | |
|---------------------|----|
| T | |
| thrust | |
| - main boundary | 65 |
| - main frontal | 64 |
| Tibetan-tethys Zone | 68 |

CHAPTER 6

| | |
|--------------------|----|
| B | |
| bearing or azimuth | 71 |
| black end | 72 |
| Brunton compass | 70 |
| bull's eye level | 72 |

| | |
|--|----|
| C | |
| compass points | |
| - magnetic north | 70 |
| - true north | 70 |
| counter clockwise - magnetic declination | 70 |

| | |
|------------------|----|
| D | |
| declination | |
| - adjustment for | 70 |
| - definition | 70 |

| | |
|---------------|----|
| dip | 72 |
| dip direction | 72 |

| | |
|--------------------|----|
| F | |
| field measurements | 70 |
| - bearing | 71 |

| | |
|-----------------------|--------|
| G | |
| geological compass | 70 |
| - its field uses | 70 |
| geological structures | 72 |
| - measuring | 72, 73 |

| | |
|----------|----|
| L | |
| lines | 72 |

| | |
|----------------------|----|
| M | |
| magnetic declination | 70 |
| magnetic north pole | 70 |

| | |
|----------|----|
| P | |
| plunge | 73 |

| | |
|----------|----|
| S | |
| slopes | 72 |
| strike | 72 |

| | |
|----------|----|
| T | |
| trend | 73 |

| | |
|---------------|----|
| V | |
| Vernier level | 73 |
| Vernier scale | 73 |

CHAPTER 7

| | |
|---------------------|----|
| A | |
| angle | |
| - between two lines | 90 |
| - determination | 90 |

| | |
|-------------|----|
| D | |
| dip | |
| - amount | 99 |
| - direction | 99 |

| | |
|--------------------|----|
| E | |
| extents of scatter | |
| - determination of | 90 |
| - around mean pole | 90 |

| | | |
|-------------------------------------|--|----|
| F | | |
| field data and statistical analysis | | 99 |

| | | |
|---|--|----|
| P | | |
| plotting | | |
| - a line contained in a plane | | 88 |
| - a pole | | 88 |
| - a plane | | 85 |
| - line of intersection of two planes | | 90 |
| - line of intersection of two planes from their poles | | 91 |
| - the pole on a pole net | | 93 |
| plotting techniques | | 83 |
| projection | | |
| - cone | | 83 |
| - line | | 77 |
| - plane | | 83 |

CHAPTER 8

| | | |
|--|--|---------------|
| A | | |
| Aerial photo | | |
| - six important elements of interpretation | | 101 |
| D | | |
| drainage | | 101 |
| - patterns of | | 102, 103, 105 |
| E | | |
| erosional agents | | |
| - interaction of | | 102 |
| F | | |
| features | | |
| - of erosion | | 102 |
| G | | |
| gray tone | | 102 |
| - elements in considering | | 102 |

| | | |
|---------------------|--|-----|
| R | | |
| rock types | | |
| - identification of | | |
| igneous | | 106 |
| metamorphic | | 107 |
| sedimentary | | 108 |

| | | |
|----------------------|--|-----|
| T | | |
| topography | | 101 |
| - characteristics | | 101 |
| - nature of landform | | 101 |

| | | |
|---------------------------------|--|-----|
| V | | |
| vegetation | | |
| - identification and evaluation | | 103 |

CHAPTER 9

| | | |
|-------------------------------|--|----------|
| C | | |
| capacity | | 117 |
| - bearing | | 117 |
| - ultimate bearing | | 117 |
| - allowable bearing | | 117 |
| - classification of soils | | 128-130 |
| cohesion | | |
| - effective | | 116 |
| consolidation | | |
| - degree of | | 116, 117 |
| D | | |
| dilatancy | | 122 |
| E | | |
| earth pressure | | |
| - active | | 118 |
| - lateral | | 117 |
| G | | |
| grain | | |
| - shape by visual examination | | 118 |
| - size by visual examination | | 118 |

| | |
|--------------------------------|-----|
| H | |
| head | 114 |
| - total of water | 114 |
| M | |
| Mohr-Coloumb Failure Criterion | 116 |
| P | |
| plasticity | |
| - index | 111 |
| - chart | 128 |
| R | |
| reaction of soils to testing | |
| - no | 122 |
| - rapid | 122 |
| - slow | 122 |
| S | |
| soil | |
| - components of | 113 |
| - definitions of | 113 |
| - degree of saturation | 113 |
| - field identification | 118 |
| - density | 112 |
| - permeability | 113 |
| soils | |
| - coarse-grained | 110 |
| - fine-grained | 110 |
| - gradation of | 111 |
| strength | |
| - high dry | 123 |
| - low dry | 123 |
| - medium dry | 123 |
| - shear | 116 |
| - shear stress | 116 |
| stress | 115 |
| - effective | 115 |
| - quick condition | 115 |
| - piping | 115 |
| - resultant body force | 115 |

| | |
|--------------|---------|
| T | |
| test methods | 123-125 |

CHAPTER 10

| | |
|----------------------------------|----------|
| B | |
| Barton's Equation | 139 |
| basic friction angle | 141 |
| J | |
| Joint Compressive Strength (JCS) | 140 |
| Joint Roughness Coefficient | 139 |
| R | |
| rock mass rating | 146 |
| rock mass joint sets | 143 |
| S | |
| shear strength | 137 |
| - peak | 139, 144 |
| - residual | 138 |
| Slope Mass Rating (SMR) | 146 |
| Surface roughness | 141 |
| U | |
| Uniaxial compressive strength | 140 |
| W | |
| water | |
| - artesian condition | 113 |
| - perched water table | 113 |
| - phreatic surface | 113 |
| - pore-water pressure | 113 |

CHAPTER 11

| | |
|--|----------|
| A | |
| apparent resistivity | 179 |
| - values | 182 |
| B | |
| blind zone | 169 |
| C | |
| critical angle | 160 |
| critical distance | 162 |
| D | |
| Darcy's law | 176 |
| depth | |
| - characteristics of near surface layers | 156 |
| detectors | 156 |
| distance graphs | 164 |
| - analysis of time | 164 |
| - direct | 164 |
| - reverse | 158 |
| E | |
| elastic constants | 154 |
| elastic waves | 154 |
| electrical sounding | |
| - field procedures | 183 |
| - procedures | 183, 184 |
| electrical trench | 182 |
| energy | |
| - explosions from source | 156 |
| G | |
| geometric constant | 179 |
| geophone | 157 |

| | |
|------------------------------------|----------|
| H | |
| homogeneous earth | 184 |
| I | |
| incompressibility | 154 |
| intercept time | 162 |
| interfaces | |
| - non-parallel | 164 |
| - parallel | 162 |
| L | |
| logarithmic scale | 183 |
| M | |
| mapping procedures | 180, 182 |
| models | |
| - inferred from seismic refraction | 166-170 |
| P | |
| plotting | 183 |
| porosity | 175, 176 |
| - definition of | 175 |
| P-waves | 154 |
| R | |
| reflection | 156 |
| refraction | |
| - total | 160 |
| resistivity method | 153 |
| rigidity | 154 |
| rocks | |
| - saturated | 176, 177 |

S

| | |
|--------------------------------|----------|
| seismic | |
| - refraction method | 153, 154 |
| - velocity | 153 |
| seismic amplifier and recorder | 158 |
| seismic refraction | |
| - uses of | 154 |
| seismogram | 158 |
| seismograph | 156 |
| shots | 156 |
| shot points | 156 |
| Snell's Law | 160 |
| stacking | 156 |

T

| | |
|--------------------------------------|-----|
| total refraction | 160 |
| true resistivity | 187 |
| - limit of zero electrode separation | 187 |

V

| | |
|------------------------------------|-----|
| Vertical Electrical Sounding (VES) | 183 |
| Velocities in rocks | 155 |

CHAPTER 12**F**

| | |
|------------|----------|
| flows | |
| - types of | 189, 190 |

L

| | |
|---------------------------|----------|
| landslides | |
| - causes of (triggers) | 192, 193 |
| - construction activities | 191, 192 |
| - deforestation | 191 |
| - earth-control of | 191 |
| - improper land use | 191 |
| - prevention + control of | 193, 194 |

| | |
|-----------------|-----|
| landslides-dams | 195 |
|-----------------|-----|

landslide-dams

| | |
|--------------|-----|
| - causes of | 194 |
| - failure of | 195 |

S**slides**

| | |
|------------|-----|
| - types of | 189 |
|------------|-----|

spreads

| | |
|------------|----------|
| - types of | 189, 190 |
|------------|----------|

V

| | |
|--|-----|
| Varne's classification (slope movements) | 190 |
|--|-----|

CHAPTER 13**A**

| | |
|-----------------------------|----------|
| analysis of slope stability | 200, 201 |
|-----------------------------|----------|

B

| | |
|----------------------|-----|
| base failure defined | 209 |
|----------------------|-----|

C

| | |
|----------------|-----|
| chart solution | 208 |
|----------------|-----|

circular failure chart

| | |
|--------------|-----|
| - derivation | 215 |
| - use of | 219 |

| | |
|--------------|-----|
| cohesion (c) | 202 |
|--------------|-----|

| | |
|---------------------|-----|
| computer programmes | 237 |
|---------------------|-----|

| | |
|-------------------|-----|
| computer solution | 208 |
|-------------------|-----|

| | | | | |
|---|---------------|--|----------------------------------|------------------|
| F | | | - partly submerged | 213 |
| Factor of safety | 203, 205, 210 | | - projected highway | 226, 237 |
| - failure slopes | 210 | | - reinforcement | 236 |
| friction circle method (FCM) | 208 | | - rock | 259 |
| | | | - soil/talus | 259 |
| | | | - surface of sliding | 209, 232 |
| | | | - toe | 217 |
| G | | | slope stability analysis | |
| groundwater | | | - the two basic approaches | 201 |
| - flow patterns | 217 | | slopes | |
| - flow assumptions | 216 | | - dry | 232 |
| | | | - failed | 210 |
| | | | - irregular on non-uniform soils | 211 |
| L | | | - stability analysis of | 200, 201 |
| landslides | | | - unfailed | 210 |
| - back analysis of | 260 | | steady state drawdown | 216 |
| - major causes of | 257, 258 | | stereoplot | 241 |
| - trigger | 257 | | stability number for soil | 206 |
| | | | - with cohesion and friction | 206 |
| M | | | stress | |
| Method of Slices (MS) | 208 | | - effective | 204 |
| | | | - normal | 203 |
| P | | | T | |
| phreatic surface | 216 | | tension crack | 229 |
| plane failure | 228 | | - as an indicator of instability | 229-230, 233-235 |
| - analysis | 229 | | topples | 228 |
| - general conditions for | 228 | | toe | |
| progressive failure | 259 | | - undercutting | 236 |
| | | | W | |
| R | | | wedge analysis | 238 |
| rockfall jumping | 260 | | - cohesion and water pressure | 243 |
| | | | wedge failure | 237 |
| S | | | wedge failure | |
| shearing strength(s) | 212 | | - analysis of | 238 |
| slides | | | - definition of | 240 |
| - in homogeneous cohesive soil | 209 | | wedge geometry | |
| slope | | | - definition of | 238 |
| - failure (defined) | 209 | | wedges stability charts | |
| - general characteristics in factor of safety | 210 | | - for friction | 245 |
| - changes in groundwater conditions | 215 | | | |
| - influence of undercutting of the toe | 236 | | | |

| | |
|-------------------|-----|
| zero | |
| - forces equal to | 212 |

CHAPTER 14

| | |
|----------------------------------|-----|
| A | |
| assessments | |
| - prefeasibility and feasibility | 264 |

| | |
|----------------|-----|
| D | |
| decision trees | |
| - review of | 267 |

| | |
|---|-----|
| detailed design | |
| - uncertainty characterisation | 265 |
| - examples of risk mitigation calculation | 265 |

| | |
|-----------------|-----|
| H | |
| hazard | |
| - definition of | 262 |

| | |
|------------------|-----|
| R | |
| risk | |
| - definitions of | 263 |

| | |
|------------------------------|-----|
| U | |
| uncertainty characterisation | 265 |

CHAPTER 15

| | |
|-------------------------|---------|
| A | |
| absorption | 283 |
| aggregates | 271-273 |
| - abrasion test | 274 |
| - bitumen affinity test | 274 |
| - alkali reaction | 274 |
| - fineness modulus | 275 |
| - friable particle test | 274 |
| - flotation test | 274 |
| - maximum density | 275 |
| - permeability | 283 |

| | |
|--|-----|
| - porosity | 283 |
| - quality requirements | 289 |
| - restrictions on deleterious constituents | 291 |
| - sieve analysis | 273 |
| - soundness test | 273 |

| | |
|-----------------|-----|
| aggregate voids | 276 |
|-----------------|-----|

| | |
|---------------------|-----|
| B | |
| bituminous mixtures | |
| - durability | 302 |
| - wettability | 303 |

| | |
|-----------------------------|----------|
| blending aggregates | |
| - two graphical methods for | 295, 296 |

| | |
|-------------------------------------|-----|
| C | |
| California Bearing Ratio Test (CBR) | 271 |

| | |
|---------------------------------------|-----|
| coarse aggregates | |
| - limits in deleterious substances in | 292 |

| | |
|----------|-----|
| coatings | 287 |
|----------|-----|

| | |
|------------|-----|
| D | |
| density | 286 |
| durability | 302 |

| | |
|------------------|-----|
| F | |
| fineness modulus | 275 |

| | |
|------------------|-----|
| G | |
| geologic history | 282 |

| | |
|----------|-----|
| H | |
| hardness | 286 |

| | |
|--------------------|-----|
| I | |
| internal structure | 282 |
| internal texture | 282 |

| | |
|---|------------------|
| M | |
| mineralogic composition | 282 |
| O | |
| oxidation, hydration & carbonation | 288 |
| P | |
| particle shape | 287 |
| Portland Cement Concrete (PCC) | 271 |
| Q | |
| quality requirements for aggregates | 273-276, 283-291 |
| S | |
| sieve analysis | 273 |
| solubility | 288 |
| soundness test | 273 |
| specifications | |
| - five important requisites | 288 |
| straight line method | 295 |
| strength & elasticity | 285 |
| surface texture | 284 |
| T | |
| tests for evaluation of quality of aggregates | |
| - thermal properties | 285 |
| V | |
| volume change | 284 |

CHAPTER 16

| | |
|--|-----|
| A | |
| aesthetics, comfort, and role of plantations | 321 |
| alternative habitat | 317 |
| apiculture | 320 |
| atmospheric pollution | 322 |
| B | |
| balanced line system | 324 |
| biological control | 318 |
| C | |
| common plant species | 332 |
| common property resources (CPR) | 318 |
| conservation of plant resources | 316 |
| conservation plantations | 317 |
| D | |
| detritus ecosystems | 314 |
| E | |
| erosion | 322 |
| estimation of transpiration rates | 372 |
| F | |
| failed slope surfaces | 316 |
| food chains | 318 |
| forest ecosystems | 314 |
| H | |
| honey plants | 326 |
| Hypophae | 320 |

| | |
|--|---------------|
| I | |
| internal mechanism to regulate water flow | 370 |
| M | |
| measurement of transpiration rates | 373 |
| multiple row planting | 324 |
| N | |
| noise pollution | 323 |
| P | |
| phreatophytes | 368 |
| plant biology | 341 |
| plant mechanics | 341 |
| plantations as part of restoration ecology | 316 |
| potometer method of measurement | 374 |
| practice support factor | 354 |
| pysimeter method | 373 |
| R | |
| rainfall energy | 345 |
| rainfall erosivity | 343 |
| restoration ecology | 316 |
| role of roadside plantation | 320-323 |
| root anchoring | 364 |
| root reinforcement model | 358 |
| roots tensile strength | 359, 362, 363 |
| S | |
| single row planting | 324 |
| slope stability | 316 |

| | |
|---|----------|
| soil erodibility | 347 |
| surcharge effect | 365, 367 |
| T | |
| topographic factor | 348 |
| transpiration | 368 |
| transpiration flux | 372 |
| transpiration mechanism (factors effecting) | 375 |
| transpiration rates (estimation of) | 372 |
| U | |
| unbalanced continuous line | 324 |
| universal soil loss equation | 342 |
| v | |
| vegetative cover factor | 351 |

CHAPTER 17

| | |
|---|----------|
| B | |
| base pressures | 396 |
| C | |
| classification of retaining walls | 377 |
| collapse load | 379 |
| computer-aided design of retaining wall | 396, 397 |
| Coulomb's Theory | 386, 388 |
| D | |
| design criteria | 389 |
| design parameters | 392 |

| | |
|---|---------------|
| E | |
| earth pressure (active and passive assumptions) | 377 |
| earth pressure on wall | 391, 394 |
| F | |
| factors | 389, 395 |
| forces on retaining wall | 392, 393 |
| forces on wall | 392 |
| forces on wedge | 392 |
| L | |
| lower bound theorem | 379 |
| M | |
| manual calculations | 397 |
| moments about heel | 400 |
| P | |
| plane strain | 377 |
| pore-water pressure | 391 |
| R | |
| Rankine Active State | 384, 386, 387 |
| retaining wall design criteria, gravity type | 389 |
| RETAIN (programme) | 396, 397 |
| U | |
| upper bound theorem | 379 |
| W | |
| wall classification | 379 |

CHAPTER 18

| | |
|---|--------------------|
| B | |
| BISAR | 420 |
| BISDEF | 422 |
| C | |
| CBR method | 415, 416 |
| CHEVNL (CHEVPC) | 420 |
| computer programmes | |
| - description & operating notes | 427 |
| criteria for failure | 417 |
| D | |
| deflection analysis (Asphalt Institute) | 467 |
| deflection criteria | 468 |
| E | |
| EL SYM 5 | 419 |
| equivalent axle load (EAL) | 411 |
| F | |
| fatigue criteria for failure | 417 |
| flexible pavement designs | 429, 430, 455, 456 |
| L | |
| layer characteristics | 419-427, 469 |
| layered-elastic analysis | 418, 419 |
| limiting failure criteria | 470 |
| M | |
| mechanistic design | |
| - advantages & disadvantages | 417 |

| | |
|---------------------------------------|-----|
| mechanistic empirical method | 421 |
| modulus of asphalt | 422 |
| modulus deviator stress | 423 |
| N | |
| non-destructive test load (NDT) | 470 |
| P | |
| PSAD2A | 421 |
| pavement structure thickness analysis | 460 |
| R | |
| rutting criteria for failure | 417 |
| resilient modulus | 421 |
| S | |
| structural number method | 416 |
| sub-grade analysis | 459 |
| summary of overlay designs | 484 |
| T | |
| traffic analysis | 460 |
| TRRL Method | 416 |

CHAPTER 19

| | |
|-----------------------------|-----|
| C | |
| California Culvert Practice | 489 |
| critical depth | 501 |
| critical flow | 500 |
| critical slope | 501 |
| critical velocity | 501 |
| curve number | 493 |

| | |
|---------------------------------------|----------|
| E | |
| energy of flow | 498 |
| equal energy depths | 501 |
| equation of continuity | 492 |
| F | |
| flow with inlet control | 505, 510 |
| flow with outlet control | 505, 510 |
| Froude Number | 505 |
| H | |
| head | |
| - potential | 498 |
| - specific | 498 |
| - velocity | 498 |
| K | |
| kinetic energy | 498 |
| M | |
| Manning Equation | 501 |
| Manning Roughness Coefficient | 497 |
| N | |
| nomograph | 509 |
| non-uniform or varied flow (problems) | 503 |
| P | |
| potential energy | 498 |
| R | |
| rainfall | |
| - frequency | 487 |
| - intensity | 480 |
| rational formula of runoff prediction | 489 |

| | |
|--------------|-----|
| U | |
| uniform flow | 495 |

| | |
|---------------|-----|
| V | |
| varied flow | 498 |
| velocity head | 498 |

CHAPTER 20

| | |
|----------------------------------|---------|
| A | |
| assessment of costs and benefits | 528,529 |

| | |
|--------------------|-----|
| B | |
| benefit cost ratio | 532 |

| | |
|-----------------------------|-----|
| C | |
| cash flow method | 531 |
| categories in cost function | 546 |

| | |
|----------------------------|---------|
| D | |
| definition of concepts | 539,540 |
| demand curve | 547 |
| direct costs or road costs | 526 |
| i) agency costs | 527 |
| ii) user costs | 527 |
| discounting | 526 |

| | |
|---------------------------------------|----------|
| E | |
| equivalent uniform annual cost method | 533, 534 |
| examples of cash flow and IRR | 553,554 |

| | |
|---------------------------|-----|
| F | |
| first year rate of return | 533 |

| | |
|------------------------|-----|
| G | |
| generalized heuristics | 531 |

| | |
|----------------------------------|-----|
| I | |
| Indirect costs or non-road costs | 527 |
| i) agency costs | 527 |
| ii) environmental costs | 527 |
| iii) user costs | 527 |
| inflation | 525 |
| internal rate of return | 533 |
| investment planning | 542 |

| | |
|----------------------------|-----|
| L | |
| long-run economic planning | 531 |
| long-run total cost | 545 |

| | |
|--|---------|
| M | |
| marginal average rate of return (MARR) | 550-552 |

| | |
|--------------------------|-----|
| N | |
| net present value | 532 |
| net present value method | 538 |

| | |
|----------------------|-----|
| P | |
| present worth method | 537 |

| | |
|--------------------------|-----|
| S | |
| shadow prices | 526 |
| short-run cost functions | 540 |
| short-run total cost | 545 |
| socioeconomic attributes | 548 |

CHAPTER 22

A

activities during prefeasibility stage
hazard and risk assessments 567

C

calculation of quantities 582

D

data sheets for hazard assessments 569-574

drainage density 568

E

Environmental Impact Assessment (EIA) 596, 597

G

groundwater conditions 568

H

hazard for road length 566

hazards and risks

- data collection for assessment 568
- preliminary assessments 567

M

map

- geological 568
- slope 568
- topographic 567

mountain roads

- prefeasibility checklist 564

P

prefeasibility economic analysis 599

preliminary hazards and risk assessments 567

problems related to staging 565

problems with geometric design 578

R

rating scheme for rural access roads 562

rock and soil types 568

S

section type 568

slope angle 568

state of nature 565

W

walk-over survey 568, 569

CHAPTER 23

B

base map preparation 613

D

drainage characteristics 607

E

environmental impact factors 644, 645

F

field mapping techniques 605

G

groundwater 607

| | |
|----------------------------------|----------|
| H | |
| hazard level | 618, 628 |
| hazard mapping methods (1 and 2) | 632 |
| helicopter photos | 604 |
| M | |
| major folds | 609 |
| maps | 615 |
| - engineering geological | 612 |
| - hydrological | 615 |
| - land use | 615 |
| - observation points | 612 |
| - slope | 612 |
| - morphostructural | 615 |
| P | |
| photo interpretation | 604 |
| plane failure | 622 |
| Q | |
| quantity estimation | 604 |
| R | |
| range of hazard rating | 618 |
| rock slope hazard attribute | 624 |
| rock slope hazard map | |
| - execution of | 635 |
| rock structure | 609 |
| rock type | 607 |
| rock weathering | 607 |
| S | |
| SHIVA | 632, 641 |
| slope attributes | 606, 642 |

| | |
|-----------------------------|-----|
| slope maps | 604 |
| soil slope hazard attribute | 626 |
| soil type | 609 |
| state of nature | |
| - data sheet | 610 |
| structural attribute rating | 633 |
| T | |
| topple failure | 624 |
| types of danger | 611 |
| type of failure | 628 |
| W | |
| wedge failure | 620 |

CHAPTER 24

| | |
|---|----------|
| A | |
| Annual Average Daily Traffic (AADT) | 729 |
| B | |
| backbreaks | 732 |
| backfill coefficients | 721, 722 |
| - type for retaining walls | 717 |
| bearing capacities | |
| - allowable for different types of soil | 718 |
| biotechnical stabilization | 673 |
| blasting | |
| - chemical | 732, 733 |
| blastholes | |
| - staggered | 733 |
| blasting design | 732 |
| blasting techniques | 732 |
| bristar | 733 |

| | |
|--|----------|
| C | |
| calmmite | 733 |
| check dams | |
| - flow through | 685 |
| - in gully control | 682 |
| - spacing | 683 |
| - spillway of | 684 |
| criteria for design of road formations | 653, 654 |
| culverts | 670, 672 |
| cut slope activities | 658, 659 |
| cut slope stability and design | 660, 669 |
| D | |
| debris control | 673 |
| deep sub-surface drainage | 671 |
| - horizontal drains | 671 |
| debris deflector | 681 |
| debris relief riser | 681 |
| debris rock | 682 |
| design of retaining walls | |
| - rule of thumb | 697 |
| - semi-empirical designs | 697 |
| - theoretical | 697 |
| detailed stage engineering | |
| - geological studies | 669 |
| detailed design | |
| - cut slopes | 650 |
| - steps in | 649, 650 |
| drainage types | 672 |
| drains | |
| - installation | 738 |
| drilling | 653 |
| E | |
| effective burden | 733 |

| | |
|--|----------|
| effective spacing | 733 |
| engineering-geological studies & mapping | 651 |
| erosion | |
| - eddy | 756 |
| - Kolk | 756 |
| explosives | 733 |
| F | |
| final alignment location | 650, 651 |
| friction factor | 719, 720 |
| frictional resistance | 723, 724 |
| G | |
| geophysical studies | 652 |
| geotechnical studies | 652, 653 |
| gully control | 671, 673 |
| - cascades for | 686 |
| H | |
| horizontal drains | |
| - drawdowns of | 89 |
| - maintenance of | 40 |
| - length and spacing | 39 |
| I | |
| influence area activities | 659 |
| L | |
| landslides | 671 |
| landslide drainage | 671, 673 |
| - specifications for landslide stabilization | 673 |
| N | |
| neat excavation | 732 |

| | |
|----------------------|-----|
| P | |
| pavement design | 727 |
| pavement | |
| - guidelines | 728 |
| - drainage | 672 |
| phreatic surface | 690 |
| pre-split blastholes | 732 |
| prima | 733 |

| | |
|---------------------------------------|----------|
| R | |
| resisting moment | 723 |
| retaining wall and breast walls | |
| - approach to design of | 690, 691 |
| - back-battered versus front-battered | 693 |
| river training | |
| - problems | 755 |

| | |
|---|----------|
| S | |
| side drains | 670 |
| slope values | 668 |
| slopes | |
| - equilibrium. cut slopes | 659 |
| - non-equilibrium or marginal equilibrium | 659 |
| slope angle | 661 |
| slope catchment | |
| - guidelines | 659 |
| soil number | 662, 662 |

| | |
|----------------------|----------|
| W | |
| walk-over survey | |
| - alignment location | 650, 651 |
| - staggered | 783 |

CHAPTER 25

| | |
|---|----------|
| B | |
| blasting techniques | 768 |
| bristar | 768 |
| C | |
| calmmite | 768 |
| contract types | |
| - characteristics associated with | 761 |
| considerations for hill road construction | 762 |
| confusion of contractor by certain contract phrases | 765, 766 |
| D | |
| details for earthwork | 768, 769 |

CHAPTER 26

| | |
|--|----------|
| A | |
| annual budget plan for urgent repairs | 772 |
| B | |
| Benkelman Beam | 792 |
| bridge damage report form and instructions for use | 799, 800 |
| D | |
| distress survey | 784 |
| E | |
| evaluation of pavements | |
| - distinct purposes | 783 |

| | |
|--|----------|
| F | |
| flexible pavement deduct values | 790, 791 |
| - friction coefficient | 793 |
| frequency of evaluation | 797 |
| H | |
| hydroplaning | 792 |
| L | |
| laboratory tests for rehabilitation | 785 |
| landslide damage report | 804 |
| - instructions for users | 805, 806 |
| M | |
| maintenance | |
| - paved roads | 772 |
| - unpaved road | 771, 772 |
| N | |
| non-destructive testing | 785 |
| P | |
| pavement condition ratings | 789 |
| pavement condition evaluations | 787, 788 |
| pavement selection process | 795 |
| pavement texture | 792 |
| pavement macro-texture | 792 |
| pavement micro-texture | 792 |
| present serviceability rating (PSR) | 784 |
| priority ranking for budget allocation | 798 |
| R | |
| rehabilitation alternatives | 796 |

| | |
|---|---------|
| road corridor management | 797 |
| road damage report form (instructions for use) | 801-803 |
| S | |
| severity levels | 773-783 |
| spalled cracks | 773 |
| T | |
| temperature | |
| - effects on response | 792 |
| W | |
| watershed management | 797 |

ANNEX 1

| | |
|--|----------|
| A | |
| alluvial fan | 813 |
| B | |
| basin | 817, 819 |
| C | |
| calcite sandstone | 809 |
| cirque | 817 |
| cirque headwall | 817, 819 |
| clay matrix sandstone | 809 |
| colluvial deposits | 811 |
| colluvial fans | 813 |
| D | |
| debris cone with detachment zone above | 813 |
| debris flows | 813 |

| | |
|---|----------|
| E | |
| erratic boulders | 826 |
| eskers | 823 |
| F | |
| fabric | 814 |
| - closed, particle supported | 814 |
| - matrix supported | 814 |
| - open work | 814 |
| - partly open works | 814 |
| fosses | 823 |
| G | |
| geological classification of soil types | 807 |
| glacial lakes | 820 |
| glacial trough | 817 |
| glacial trough | 819 |
| - cross-profile of | 819 |
| glacially-fed streams | 820 |
| glacio-fluviatile forms | 822 |
| glacio-fluviatile sediments | 815 |
| gneiss group | 810 |
| gradation | 813 |
| granular disintegration | 810 |
| H | |
| hanging valley | 817 |
| headwall | 817, 819 |
| horns | 817 |
| I | |
| impervious horizon | 808 |

| | |
|-----------------------------|----------|
| K | |
| Kame terraces | 823 |
| kettles | 823 |
| L | |
| limestones | 809 |
| M | |
| moraines | 815 |
| - end | 815 |
| - front | 816, 820 |
| - ground | 815 |
| - lateral | 815, 820 |
| - lodgement | 816 |
| - recessional | 820 |
| N | |
| nine-unit surface model | 815 |
| O | |
| outwash fans (deltas) | 823 |
| P | |
| passes | 817 |
| Q | |
| quartzite | 810 |
| R | |
| residual soils | |
| - classification of | 809, 810 |
| reworked glacial deposits | 811 |
| reworked colluvial material | 811 |
| rhythmite | 823 |
| rock avalanche tongue | 813 |

| | |
|---------------------------|----------|
| rockfall | 813 |
| rockslide | 813 |
| S | |
| sandstone group | |
| - schist | 810 |
| - scree | 811 |
| - shale | 809 |
| slides | |
| - rotational | 811 |
| - translational | 809, 811 |
| slope (transport limited) | 813 |
| stairs | 817 |
| I | |
| talus deposits | 813 |
| threshold | 819 |
| truncated spurs | 817 |
| V | |
| varves | 823 |

The opinions expressed in this publication are those of the author(s) and do not necessarily reflect the views of the International Centre for Integrated Mountain Development.

The designations employed and the presentation of the material in this publication do not imply the expression of any opinion whatsoever, on the part of the International Centre for Integrated Mountain Development, concerning the legal status of any country, territory, city, or area of its authorities; or concerning the delimitation of its frontiers and boundaries.

Founding of ICIMOD

The fundamental motivation for the founding of the first International Centre in the field of mountain area development was widespread recognition of the alarming environmental degradation of mountain habitats, and consequent increasing impoverishment of mountain communities. A coordinated and systematic effort on an international scale was deemed essential to design and implement more effective development responses to promote the sustained well-being of mountain communities.

The establishment of the Centre is based upon an agreement between His Majesty's Government of Nepal and the United Nations Educational, Scientific, and Cultural Organisation (UNESCO) signed in 1981. The Centre was inaugurated by the Prime Minister of Nepal in December, 1983, and began its professional activities in September, 1984.

The Centre, located in Kathmandu, the capital of the Kingdom of Nepal, enjoys the status of an autonomous international organisation.

Director : Dr. E. F. Tacke

Deputy Director : Dr. R. P. Yadav

Participating Countries of the Hindu Kush-Himalayan Region

- | | |
|---------------|--------------|
| o Afghanistan | o Bangladesh |
| o Bhutan | o Myanmar |
| o China | o India |
| o Nepal | o Pakistan |



**INTERNATIONAL CENTRE FOR
INTEGRATED
MOUNTAIN DEVELOPMENT (ICIMOD)**
4/80 Jawalakhel, G.P.O. Box 3226,
Kathmandu, Nepal

Telex : 2439 ICIMOD NP
Cable : ICIMOD NEPAL
Telephone : 525313
Fax : 524509

