

LETTER • **OPEN ACCESS**

Early twenty-first century satellite-driven irrigation performance in the world's largest system: Pakistan's Indus Basin irrigated system

To cite this article: Jorge L Peña-Arancibia and Mobin-ud-Din Ahmad 2021 *Environ. Res. Lett.* **16** 014037

View the [article online](#) for updates and enhancements.

ENVIRONMENTAL RESEARCH
LETTERS

LETTER

OPEN ACCESS

RECEIVED
27 August 2020REVISED
17 November 2020ACCEPTED FOR PUBLICATION
8 December 2020PUBLISHED
29 December 2020

Original content from
this work may be used
under the terms of the
[Creative Commons
Attribution 4.0 licence](#).

Any further distribution
of this work must
maintain attribution to
the author(s) and the title
of the work, journal
citation and DOI.



Early twenty-first century satellite-driven irrigation performance in the world's largest system: Pakistan's Indus Basin irrigated system

Jorge L Peña-Arancibia and Mobin-ud-Din Ahmad

CSIRO Land and Water, GPO Box 1700, Canberra ACT 2601, Australia

E-mail: jorge.penaarancibia@csiro.au and mobin.ahmad@csiro.au**Keywords:** remote sensing, evapotranspiration, variability, equity, CMRSET, SEBAL, ETLookSupplementary material for this article is available [online](#)**Abstract**

Evaluating irrigation performance in large systems is often limited by the availability of reliable water use data. Satellite-driven actual evapotranspiration (ET_a) estimates are used herein as water use surrogates to assess the year-to-year inter-seasonal irrigation performance in 46 canal commands in the Indus Basin irrigated system (IBIS), the largest in the world ($\sim 160\,000\text{ km}^2$). The accuracy and reliability of the ET_a estimates are verified using two previously published locally adjusted satellite-driven ET_a estimates, as well as field ET_a estimates. Inter-seasonal variability (canal command water use in time) and equity (inter- and intra-canal command water use) are assessed from 2000 to 2018 using violin-plots time-series for the two irrigation seasons, the wet 'Kharif' and dry 'Rabi'. The violin-plots probability density functions are used to assess intra-canal command equity; and their seasonal time-series to assess inter-seasonal variability. The long-term multi-year assessment conducted here, the first for the IBIS using consistent satellite-driven ET_a time-series, shows that canal commands with ready access to groundwater exhibit more equity and less inter-seasonal variability when compared to canal commands chiefly reliant on surface water supplies; with the latter showing intra-canal command inequities between head-end and tail-end irrigated areas. Also, ET_a in canal commands is mostly slightly increasing and there is low inter-seasonal variability in both irrigation seasons, except for two canal command at the system-end, which show higher inter-seasonal variability and inequity than their upstream counterparts. The methods employed here can be used in large irrigated systems elsewhere to assess ongoing irrigation performance and to verify results of targeted (non)structural irrigation management.

1. Introduction

Increased reliance of surface and groundwater to meet the demand for food and other agricultural products is placing water resources on an unsustainable trajectory in many parts of the world (Gleeson and Wada 2013, Wada and Bierkens 2014). The largest irrigated system in the world, the Indus Basin irrigated system (IBIS, $\sim 160\,000\text{ km}^2$, FAO 2012) in Pakistan is arguably on this trajectory; with declining groundwater levels and salinity impacting water availability and crop productivity (Briscoe and Qamar 2005, Khan *et al* 2017, Kirby *et al* 2017 and references therein). The IBIS is the lifeline of Pakistan, serving $\sim 90\,000$ farmers and providing food and economic security for ~ 207 million people (FAO 2012). The Chenab, Jhelum, Kabul and Indus rivers provide inflows

($\sim 159.3\text{ km}^3\text{ yr}^{-1}$) to the IBIS, whereas flows from the Sutlej Ravi and Beas rivers ($\sim 7.8\text{ km}^3\text{ yr}^{-1}$ inflow into Pakistan) are largely diverted to India as per the Indus Water Treaty (UN 1960, IRSA 2020). To mitigate the diversions to India, the Mangla Dam (current capacity of $\sim 9.1\text{ km}^3$, storing 36% of the total inflows) and Tarbela Dam (current capacity of $\sim 7.4\text{ km}^3$, storing 12% of the total inflows), 16 barrages, 14 inter-river link canals and $\sim 60\,000\text{ km}$ of main canals were built to provide controlled irrigation to ~ 16 million ha (FAO 2012, Stewart *et al* 2018, Ahmad *et al* 2020a). For a detailed schematic diagram of the IBIS (depicting the system as of 2020) refer to figure A1 in Ahmad *et al* (2020a).

Surface water resources in the IBIS are allocated seasonally at the provincial level—combining a complex procedure of water resource assessment

and forecasting—and then to canal command areas grouped in management zones (MZs) (GOP 1991). The irrigation system is supply-based, originally designed to support one crop per year while achieving equity of surface water supply between users proportional to their landholding (Ahmad *et al* 2009). With groundwater development over the last five decades (mainly in the Punjab province) (Kirby *et al* 2017), irrigated area and crop intensity increased (Ahmad *et al* 2014a). Water conveyed to farmers through an extensive canal network follows a time-based (generally seven-day) rotational system, where in order to achieve equity in surface water supplies (Bandaragoda 1998) each farmer can take the entire flow of the outlet for a period proportional to their land area and not by crop demand. Depending on the availability of water resources, this commonly results in seasonal differences in the cropped area and/or deficit irrigation practices (Ahmad *et al* 2019). In times of water shortage, farmers either apply deficit irrigation and/or use groundwater (where possible).


Assessing irrigation performance in large systems like the IBIS is complex because of the gaps in water supply and demand information (Bhatti *et al* 2019, Bierkens and Wada 2019). Several performance metrics have been proposed to evaluate irrigation systems (Burt *et al* 1997, Karimi *et al* 2012). Equity is the key performance indicator used in the IBIS management. Traditionally, equity is calculated from canal water supply (i.e. cumecs per hectare), but flow monitoring stations and associated data in the IBIS are not generally available for all irrigation outlets, have limited geographic spread, or require laborious compilation and harmonization by various line agencies (Anwar and Bhatti 2018). In a water-scarce system like the IBIS, equity in water use is more relevant for farmers and local to national management and can be computed from satellite-driven actual evapotranspiration (ET_a). Satellite-driven ET_a has long been recognised as a robust and cost-efficient approach to quantify overall water use and monitor water management practices (Bastiaanssen and Bos 1999). By including all possible sources of water depletion (including irrigation supply, water from rainfall and soil water) in a spatially-explicit way, satellite-driven ET_a provides a more complete picture about the state of water resources in an irrigated area than canal water supply alone (Bastiaanssen and Bos 1999). Satellite-driven ET_a was used in a limited number of canal commands in the IBIS for assessing irrigation performance (Ahmad *et al* 2009, Usman *et al* 2015, Shah *et al* 2016). ET_a characteristics were assessed in the IBIS (or large parts thereof) using locally adjusted satellite-driven models (Bastiaanssen *et al* 2002, 2012, Ahmad *et al* 2008, 2009, Liaqat *et al* 2015, Simons *et al* 2020). Except for the 8 year data period used in Simons *et al* (2016) to assess the long-term water balance components in the system, the other cited studies estimated ET_a for a particular year only. The

IBIS has large spatial and temporal precipitation variability (Cheema and Bastiaanssen 2012), high and variable evaporative demand (Bastiaanssen *et al* 2002, Ahmad *et al* 2019), high seasonal variability in inflows (Archer 2003), variability of the naturally saline soils (Qureshi and Barrett-Lennard 1998) and variability in groundwater quality and use (Qureshi *et al* 2014, Ahmad *et al* 2014b), which all lead to variable cropping systems (Cheema *et al* 2020). Besides these dynamic atmospheric and landscape processes, infrastructure projects enhancing the IBIS's irrigation network, regulation and management continue to be implemented (Young *et al* 2019). To this day, no study has attempted to describe the time-series inter-seasonal ET_a or irrigation performance dynamics of the IBIS. The aim of this letter is, for the first time, to assess two metrics of irrigation performance, seasonal irrigation variability and equity in the early 21st century (2000–2018) for the 46 IBIS operational canal commands downstream of the Tarbela and Mangla dams (figure 1). Verified satellite-driven ET_a estimates are used for this purpose. The assessment is conducted for the two main irrigation seasons: wet summer 'Kharif' (April to September) and dry winter 'Rabi' (October to March). The approach utilises only the characteristics of the probability density function (PDF) of the ET_a pixels within the canal command to assess the irrigation performance metrics.

2. Materials and methods

ET_a estimates (500 m resolution) for the IBIS were computed on a 10-day basis via the CMRSET (CSIRO MODIS ReScaled EvapoTranspiration) ET_a model (Guerschman *et al* 2009), from February 2000 to December 2018 (Peña-Arancibia *et al* 2020a). CMRSET was positively evaluated in several studies under different climates and over a range of land covers (Simons *et al* 2016, Karimi *et al* 2019, Paca *et al* 2019, Weerasinghe *et al* 2020, Peña-Arancibia *et al* 2020b).

CMRSET scales reference evapotranspiration (ET_0) via a crop factor obtained from the Enhanced Vegetation Index (EVI) (Huete *et al* 2002) and the Global Vegetation Moisture Index (GVMI) (Ceccato *et al* 2002). The IBIS ET_a estimates used 10-day cloud free EVI and GVMI composites obtained via Google Earth Engine (Gorelick *et al* 2017) from the daily moderate resolution imaging spectroradiometer (MODIS) surface spectral reflectance product (MOD09GA collection 6, Vermote and Wolfe 2015). The 10-day vegetation indices were gap-filled (as needed) by harmonic analysis of time series (Zhou *et al* 2015). ET_0 was estimated using the Hargreaves (1974) equation from a combination of local gridded ~ 2.5 km temperature analysis and post-processed GLDAS ~ 25 km reanalysis data (see Peña-Arancibia *et al* 2020a for details; Rodell *et al* 2004). To assess their suitability for the analyses conducted



herein, CMRSET ET_a estimates were verified (both within year variations and spatial consistency) at the canal command scale against two locally calibrated 1 km MODIS-driven monthly ET_a datasets previously implemented in the IBIS (or part thereof): ETLook (Bastiaanssen *et al* 2012, Cheema 2012) and SEBAL (Ahmad *et al* 2008). The supplementary material provides a detailed description of the verification of the ET_a estimates used herein, and Peña-Arancibia *et al* (2020a) provide additional details on the implementation and verification. CMRSET ET_a also compared favourably in magnitude and seasonality against *in-situ* Bowen ratio ET_a measurements at two different locations in the Punjab (Peña-Arancibia *et al* 2020a).

Two irrigation performance metrics, seasonal variability and equity were assessed using ET_a as a proxy for water use based on the concepts of Bastiaanssen *et al* (1996) and Siddiqi *et al* (2018): (a) *Seasonal variability* is defined as the degree of temporal consistency in seasonal inter- and intra-canal command water use, and can be inferred from past seasonal estimates of ET_a . (b) *Equity* is defined as the inter- and intra-canal command variability of water

use for a particular season and can be inferred by the spatial variability of the ET_a estimates within the boundaries of the canal command. It is noted that ET_a does not equate to canal deliveries as water can be lost to recharge and return flows (Ahmad *et al* 2014a). Also, ET_a can be supplemented from groundwater extractions in some canal commands with access to good quality groundwater (Ahmad *et al* 2005). Using only ET_a derived metrics cannot address the *adequacy* of water supply to satisfy crop water demand (Moran 1994). However, in a system in which *equity* is the primary management aim and deficit irrigation is commonplace; the proposed performance metrics are suitable to assess irrigation performance and inform irrigation management.

Evaluating ET_a within canal command areas in time and space therefore can provide a way to diagnose seasonal variability and equity. Time-series of violin-plots (Hintze and Nelson 1998) are used for this purpose, alongside the coefficient of variation (CV, the ratio of the standard deviation to the mean expressed here as a percentage). Violin-plots combine traditional summary statistics of box plots and the shape of the PDF in a single plot, making them useful

to assess the dynamics of PDFs both in space and time. The violin-plots are used to assess the intra- and inter-seasonal variability of a canal command, all pixels within a canal command boundary are included to capture the inherent variability of the existing land cover in space and time. The variability in a given season may include expanding or contracting irrigated fields (depending on the water resource availability or construction/abandonment of canal infrastructure) or encroachment of semi or urban areas on agricultural land. The assessment is largely independent of the accuracy of the ET_a estimates if these are sensitive to the seasonal variations and magnitudes of the different land covers present in the IBIS, and do not show systematic biases. The verification (see supplementary material) of the IBIS CMRSET ET_a estimates (Peña-Arancibia *et al* 2020a) used herein confirmed they are fit-for-purpose.

The seasonal non-parametric Mann–Kendall test (Hirsch *et al* 1982) and the Sen-slope method (Sen 1968) were used to investigate trends in the seasonal ET_a time-series, both per-pixel and aggregated to the canal command scale.

3. Results

3.1. Diagnosing seasonal variability and equity using violin-plots

Three representative canal commands areas, in locations with different irrigation management, were chosen to illustrate how seasonal variability and equity can be interpreted using violin-plots from the ET_a PDFs (figure 2). The three canal commands have long distances (>20 km) between head-end and tail-end irrigators to test equity. The season chosen is the wet Kharif, when high water demand crops (e.g. rice and cotton) are grown. The first canal command assessed, the Upper Chenab Canal-Internal (UCC-INT) canal command (area 3 in figure 1), is in the upper IBIS, precipitation is ~ 520 mm yr^{-1} , surface water irrigation deficits are normally met by pumping groundwater (Ahmad *et al* 2009, 2014b). Rice and wheat are the major crops in the Kharif and Rabi seasons, respectively. The PDF of Kharif ET_a shows that generally $ET_a > 400$ mm $season^{-1}$, with most pixels having an $ET_a > 500$ mm $season^{-1}$. The intra-canal command CV is low at 8.95%. The violin plot shows that UCC-INT can be classified as a reasonably equitable canal command, if both surface and groundwater are considered. Variability can be explained by the temporal changes reported in the time-series of Kharif ET_a violin-plots. If the shape and magnitudes are relatively maintained through time, then UCC-INT can be classified as having low seasonal variability.

The second canal command assessed, the Abbasia canal command (area 30 in figure 1), is in the middle IBIS, precipitation is ~ 189 mm yr^{-1} , there is little groundwater pumping to supplement surface

water supplies due to marginal to poor groundwater quality (Ahmad *et al* 2014b). Cotton and wheat are the major crops in the Kharif and Rabi seasons, respectively. The PDF of Kharif ET_a shows reasonably high ET_a variability. Very low ET_a (< 100 mm $season^{-1}$) can be attributed to the desert areas to the south of the canal command. However, tail-end areas covered by the irrigation network also show low (< 300 mm $season^{-1}$) ET_a . Most pixels have $ET_a > 400$ mm $season^{-1}$. The intra-canal command CV is high at 49.59%. Although some of the CV can be explained by the desert areas, the Abbasia canal command can be classified as reasonably inequitable.

The third canal command assessed, the Pinyari canal command (area 46 in figure 1), is at the IBIS system-end, precipitation is ~ 154 mm yr^{-1} , groundwater is of poor quality and therefore there is little or no pumping to supplement surface water supplies (Ahmad *et al* 2014b). Rice and wheat are the major crops in the Kharif and Rabi seasons, respectively. The PDF of Kharif ET_a shows high ET_a variability. Very low ET_a (< 100 mm $season^{-1}$) can be attributed to the desert areas south of the canal command. However, many of the tail-end areas covered by the irrigation network show low (< 300 mm $season^{-1}$) ET_a . ET_a is highly variable, and in most pixels, it generally ranges from 200–450 mm $season^{-1}$, low when compared to the other two canal commands. The intra-canal command CV is high at 45.18%. Note that the Pinyari canal command CV is lower than the Abbasia canal command, but it is evident that because of the variability shown in the shape of the violin plot (i.e. the large widths with ET_a in the range of 300–400 mm $season^{-1}$ in figure 2(i) compared with those for this ET_a range in figure 2(f)) it is overall more inequitable. This occurs because the distributional characteristics between canal commands vary and CV is not a robust estimator when data are not distributed normally (Ospina and Marmolejo-Ramos 2019).

3.2. IBIS ET_a spatial and temporal variability and equity

Figure 3 shows the spatial characteristics of mean annual (cropping year, April to next March), mean Kharif and mean Rabi ET_a , respectively. Figure 3 also shows spatial ET_a trends (computed using Sen-slope per pixel) and ET_a CV. Spatial differences in mean ET_a are more noticeable during the wet Kharif season, with relatively higher values in the Punjab mixed zone serviced by the Sidhnai Barrage (~ 500 mm $season^{-1}$, orange hues in figure 1, see table S1 for details), and in the Sindh rice area serviced by the Guddu Barrage (~ 530 mm $season^{-1}$, dark blue hues in figure 1). The lower values are at the system-end canal commands serviced by the Kotri Barrage (~ 395 mm $season^{-1}$, green hues in figure 1). Dry Rabi ET_a values are less variable, with relatively higher values in the Sindh rice zone serviced by the Sukkur Barrage (~ 430 mm $season^{-1}$, red hues in





figure 1). Trends in both seasons seem to be generally slightly increasing ($5\text{--}10\text{ mm season}^{-1}\text{ yr}^{-1}$), except for the high increases ($>10\text{ mm season}^{-1}\text{ yr}^{-1}$) in the Chashma Right Bank Canal in Khyber Pakhtunkhwa and Punjab provinces during Kharif (areas 18 and 19 in figure 1). There are also decreases ($5\text{--}10\text{ mm season}^{-1}\text{ yr}^{-1}$) in the Sindh rice areas served by the Guddu and Sukkur barrages. The CV shows mostly low values ($<20\%$) in areas covered by the irrigation canal network.

The Kharif ET_a violin-plots time-series for the 46 canal commands are shown in figure 4. The statistics reported for each time-series are the mean annual CV (in %), the Sen-slope trend (in $\text{mm season}^{-1}\text{ yr}^{-1}$, computed as the trend of the spatial mean ET_a values) and the trend p value. The canal commands in the third and fourth row in green correspond to the Punjab SVC MZ and are used as an illustrative example because they show some variation

in the PDF shapes and some variability. ET_a is increasing significantly ($p < 0.01$) in all canal commands (mean of $4.8\text{ mm season}^{-1}\text{ yr}^{-1}$ range $3.37\text{--}8.96\text{ mm season}^{-1}\text{ yr}^{-1}$). CVs are low on average (mean of 15.70% , range $9.70\%\text{--}33.20\%$). The time-series mean ET_a is noticeably increasing in Karanga, LDC, UPC + UMC, FC and UBC + QC (areas 10, 12, 13 and 14 in figure 1). These canal commands can be considered with low variability and equitable. The PDF in ESC (area 15 in figure 1) shows more variability on a season-to-season basis, this canal command is at the edge of the system and adjacent to desert areas with irrigation expanding therein (Kirby and Ahmad 2016), as the PDF shape in later seasons has generally higher ET_a values in the lower range (see the areas with low ET_a in figure 3(d) alongside the increasing ET_a trends in figure 3(e) for this canal command). Other canal commands in different MZs also share ESC's characteristics (the Thal canal



command, LBC, Abbasia, PFC, Ghotki, NWC, Dadu, U Nara, respectively areas 17, 29, 30, 32, 36, 37, 39, 43 in figure 1). These canal commands can be considered with reasonable variability and reasonably inequitable. CRBC-P (area 19 in figure 1) is a special case, it shows a steady increase in mean and PDF ET_a , becoming more stable in later seasons. CRBC-P was completed in 2003 thus expanding the irrigation frontier (Atta-Ur-Rahman and Khan 2008).

It is readily apparent that in the Punjab FLC MZ (two first rows in blue hues), the canal commands with access to groundwater to supplement surface water shortfalls have less variability and are relatively equitable. The PDFs are generally narrowly concentrated around the median, and median ET_a

values do not vary much seasonally, CVs are low on average (mean of 10.90%, range 7.60%–15.16%). Some canal commands particularly in the Indus mixed MZ (orange hues, see particularly URC, Haveli, Sidhnai) also have these characteristics, they have access to groundwater and inter-river transfers from the Indus River (Ahmad *et al* 2014b). Canal commands in other MZs further downstream, generally show PDFs that are oblong around the median, which means more intra-canal command variability in ET_a and hence relatively less equity. This can be seen in all the canal commands in the Sindh Guddu Barrage MZ (dark blue hues), Sindh Sukkur Barrage MZ (red hues). There are no drastic changes in the shapes of the canal command PDFs or drastic




Figure 4. Violin-plots time-series ET_a in mm season⁻¹ for Kharif (April to September) for the 46 IBIS canal commands. Information includes canal ID, name, mean coefficient of variation CV (%) and trend S (mm season⁻¹ yr⁻¹, * indicates $p < 0.05$ and + indicates $p < 0.10$). The numbers in the X-axis correspond to the cropping year (April to next March) from 2000–2001 (00–01) to 2017–2018 (17–18). Canal commands color-coded according to an established management zone (MZ, see figure 1 and table S1 in supplementary material).



Figure 5. Idem. as figure 4 but for the Rabi season (October to March).

changes in the median values; hence although relatively less equitable, the inter-season variation is low. In the Sindh Kotri and Kalri barrages MZ, the Kalri and Lined canal commands show very similar PDFs and medians over the years. Although ET_a means are relatively lower, these canals can be considered of low variability and relatively equitable. Conversely, Pinyari and Fuleli show changes in both PDFs and ET_a means over the years, thus these canal commands can be considered of high variability and relatively less equitable. There are significant (decreasing) increasing trends ($p < 0.01$) in ET_a in (2) 32 canal commands.

The Rabi violin-plots time-series for the 46 canal commands (figure 5) show similar patterns as the Kharif violin-plots, but overall, there seems to be more intra-canal command equity as PDFs do not change drastically (even for Pinyari and Fuleli). There are less variations, and slight significant increasing trends ($p < 0.01$) in ET_a in 24 canal commands.

4. Discussion

This study used satellite-driven ET_a to provide a consistent spatiotemporal way to assess two commonly used irrigation performance metrics, seasonal variability and equity, in the 46 canal commands in the IBIS. The main advantage is arguably that satellite and meteorological data needed to estimate ET_a are readily available online or through the developers, or more recently via Google Earth Engine (e.g. Zhang *et al* 2019). Monthly CMRSET ET_a data from March 2000 to December 2018 for the IBIS area subtending the canal commands (figure 1) at 500 m resolution are available to the public via the CSIRO Data Access Portal (see data availability statement) <https://doi.org/10.25919/18h2-vf51>. The ET_a data was used to estimate the time-series water balance for the canal commands in the IBIS (Ahmad *et al* 2020a), thus providing information on magnitudes and trends of rainfall, ET_a , canal deliveries, groundwater levels and unaccounted inflows and outflows.

Satellite-driven methods that rely solely on routinely used vegetation indices to estimate ET_a have known limitations (Glenn *et al* 2010). Satellite-driven ET_a estimates are most accurate for homogeneous land covers. At 500 m resolution, a MODIS pixel is much larger than the average irrigation field in the IBIS, thus the large land cover heterogeneity is expected to result in less ET_a accuracy (Glenn *et al* 2011). The time-lag between the onset of vegetation moisture stress and its manifestation through vegetation indices can result in higher ET estimates than those measured, for example, by complex soil-vegetation-atmosphere transfer models (Kustas and Anderson 2009). In addition, the accuracy of satellite-driven ET_a models is related to the accuracy of the ground methods on which they are calibrated (Glenn *et al* 2011). CMRSET was calibrated with flux tower

data, which have an accuracy of 10%–30%. Under semi-arid conditions in Australia (similar to those in the IBIS), CMRSET ET_a estimates had comparable or better accuracy than other satellite-driven ET_a models, when compared to flux tower data (Guerschman *et al* 2009). An independent evaluation of CMRSET using long-term catchment water balance data from 227 Australian catchments also showed an accuracy (in terms of the root mean squared error) of $\sim 20\%$ with no significant biases (Guerschman *et al* 2009). Regardless of the uncertainty in CMRSET's ET_a accuracy, the nature of the present assessment relies on the inter-seasonal patterns of ET_a within and between canal commands. If these ET_a estimates are sensitive to the seasonal variations and magnitudes of the different land covers present in the IBIS (as described in the supplementary information), they provide reliable understanding of canal command seasonal variability and equity, and hence are useful for irrigation management. Although the 500 m MODIS spatial resolution may be insufficient to assess irrigation performance for individual irrigation fields, it is suitable at the canal command scale. It is possible to improve the spatial resolution for areas that require more detail using data from the recently launched satellites like Landsat 8 (30 m) and the Sentinel-2 (10 m) satellite constellations, alongside blending techniques that make use of medium-resolution-high-frequency MODIS data with high-resolution-low-frequency Landsat/Sentinel 2 data (Emelyanova *et al* 2012). The method can also be used to assess if targeted (non)structural irrigation management has any influence on ET_a variability and equity. This assessment of the management of the nearly fully utilized IBIS (Kirby *et al* 2017, FAO 2019, Ahmad *et al* 2020a) revealed that it experienced low inter-seasonal variability but with inequity (to varying degrees) in canal commands that did not have ready access to groundwater (particularly in Sindh). High variability and relatively low equity were found in canal commands at the system-end, mainly during Kharif. This result concurs with Hassan *et al* (2019), that analysed reliability in Sindh using flows in the Sindh barrages. It was found that ET_a is increasing in most canal commands during Kharif. Temperature, the basis of the Hargreaves reference ET_0 used herein in the absence of more spatially resolved data, may not be the strongest control of ET_a as indicated by experimental studies elsewhere (Donohue *et al* 2010, Hobbins *et al* 2012). Moreover, although 19 years of ET_a estimates were used in the assessment, thereby capturing this century's management rules, climate variability is captured only to an extent (Cook *et al* 2013).

Irrigated agriculture has expanded in recent decades in Punjab, chiefly because of groundwater pumping (Ahmad *et al* 2014b, 2019), whilst canal command water deliveries remained essentially constant (Ahmad *et al* 2020c). Although our

study suggest that groundwater use has achieved low variability and equity in most Punjab canal commands, there are concerns about the sustainability of groundwater because of large decreases in groundwater tables in some canal commands (Watto and Mugeru 2016). Recent studies (Young *et al* 2019, Simons *et al* 2020) suggest groundwater withdrawals are compensated somewhat by recharge, but there is evidence from GRACE total water storage anomalies and hydrological modelling that this balance maybe tilting to an unsustainable situation (Wada *et al* 2012, Iqbal *et al* 2017). Water balance modelling for the IBIS by Ahmad *et al* (2020a), which used long-term observations on groundwater levels, confirmed that water use is becoming less sustainable in several canal commands, especially in the Punjab province. The challenges are further exacerbated by changes in the seasonality and amounts of rainfall, and by rapidly reducing current limited (~10% of mean annual flows) water storage capacity due to sedimentation (Ahmad *et al* 2020b, 2020c).

5. Conclusion

This study showcased how long-term satellite-driven ET_a , and a visual representation summarizing the inter- and intra-canal command ET_a pixel variability through violin-plots, can be used as a pragmatic proxy to infer irrigation variability and equity in large irrigation systems, two metrics commonly used to assess irrigation performance. The assessment conducted per irrigation season (wet 'Kharif' and dry 'Rabi') in the 46 IBIS canal commands areas (~160 000 km²) from 2000 to 2018, shows clear patterns: (a) canal commands that supplement canal water supply with groundwater are reasonably of low variability and equitable (mostly in the Punjab province); (b) canal commands in most MZs that rely mostly on canal water supply have low variability over the years, and show intra-canal command inequities; (c) canal commands at the system-end are outstanding in that they can have high variability and also show variable intra-canal command inequities. While good quality groundwater can make up for shortfalls in canal water supply in some canal commands and improve equity, its use over time can become unsustainable and hamper irrigation management goals. The use of satellite-driven ET_a time-series provides an opportunity for monitoring irrigation dynamics and the assessment of structural and policy improvements on irrigation performance, in the IBIS and irrigated systems elsewhere.

Data availability statement

The data that support the findings of this study are openly available at the following URL/DOI:

<https://doi.org/10.25919/18h2-vf51> (Peña Arancibia and Ahmad 2020).

Acknowledgments

This work contributes to the Australian Government's Department of Foreign Affairs and Trade (DFAT) South Asia Sustainable Development Investment Portfolio (SDIP) Indus project in Pakistan and is supported by the Australian Aid Program. The authors acknowledge Maryam Ahmad and Tim McVicar (both at CSIRO Land and Water) and two anonymous reviewers for valuable comments. The IOP peer-review team, led by Editor John Keen, is gratefully acknowledged for handling the review process.

ORCID iDs

Jorge L Peña-Arancibia  <https://orcid.org/0000-0002-4952-9293>

Mobin-ud-Din Ahmad  <https://orcid.org/0000-0002-2905-5991>

References

- Ahmad M D, Gamage N, Vithanage J, Masih I, Muthuwatte L, Gunasinghe S and Hussain A 2008 Assessing the impact of physical and management interventions through RS/GIS tools on irrigation system performance in Punjab Pakistan (Final Report 2008) (Colombo, Sri Lanka: International Water Management Institute)
- Ahmad M D, Peña-Arancibia J L, Stewart J P and Kirby J M 2020a Water balance trends in irrigated canal commands and its implications for sustainable water management in Pakistan: evidence from 1981 to 2012 (accepted) *Agric. Water Manage.* (<https://doi.org/10.1016/j.agwat.2020.106648>)
- Ahmad M D, Stewart J P, Peña Arancibia J L and Kirby J M 2020b Sindh water outlook: impacts of climate change, dam sedimentation and urban water supply on irrigated agriculture p 52 (Australia) (available at: <https://publications.csiro.au/publications/#publication/PIcsiro:EP20475>) (Accessed July 2020)
- Ahmad M D, Stewart J P, Peña Arancibia J L and Kirby J M 2020c Punjab water outlook: impacts of climate change and dam sedimentation on water for irrigated agriculture p 50 (Australia) (available at: <https://publications.csiro.au/publications/#publication/PIcsiro:EP20613>) (Accessed July 2020)
- Ahmad M D, Turrall H and Nazeer A 2009 Diagnosing irrigation performance and water productivity through satellite remote sensing and secondary data in a large irrigation system of Pakistan *Agric. Water Manage.* **96** 551–64
- Ahmad M-U D, Kirby M, Islam M S, Hossain M J and Islam M M 2014b Groundwater use for irrigation and its productivity: status and opportunities for crop intensification for food security in Bangladesh *Water Resour. Manage.* **28** 1415–29
- Ahmad M-U-D, Bastiaanssen W G M and Feddes R A 2005 A new technique to estimate net groundwater use across large irrigated areas by combining remote sensing and water balance approaches, Rechna Doab, Pakistan *Hydrogeol. J.* **13** 653–64
- Ahmad M-U-D, Kirby J M and Cheema M J M 2019 Impact of agricultural development on evapotranspiration trends in the irrigated districts of Pakistan: evidence from 1981 to 2012 *Water Int.* **44** 51–73

- Ahmad M-U-D, Masih I and Giordano M 2014a Constraints and opportunities for water savings and increasing productivity through resource conservation technologies in Pakistan *Agric. Ecosyst. Environ.* **187** 106–15
- Anwar A A and Bhatti M T 2018 Pakistan's Water Apportionment Accord of 1991: 25 years and beyond *J. Water Resour. Plan. Manage.* **144**
- Archer D 2003 Contrasting hydrological regimes in the upper Indus Basin *J. Hydrol.* **274** 198–210
- Atta-Ur-Rahman and Khan A N 2008 Application of a checklisting technique for the assessment of impacts of the Chashma Right Bank Canal on land use and cropping pattern of D.I. Khan district, Pakistan *Irrig. Drain.* **57** 165–73
- Bandaragoda D J 1998 Design and practice of water allocation rules: lessons from warabandi in Pakistan's Punjab Research Report 17 p 34 (Colombo, Sri Lanka: International Irrigation Management Institute) (available at: www.iwmi.cgiar.org/Publications/IWMI_Research_Reports/PDF/PUB017/REPORT17.PDF) (Accessed August 2020)
- Bastiaanssen W G M, Ahmad M D and Chemin Y 2002 Satellite surveillance of evaporative depletion across the Indus Basin *Water Resour. Res.* **38** 9/1–9/9
- Bastiaanssen W G M and Bos M 1999 Irrigation performance indicators based on remotely sensed data: a review of literature *Irrig. Drain. Syst.* **13** 291–311
- Bastiaanssen W G M, Cheema M J M, Immerzeel W W, Miltenburg I J and Pelgrum H 2012 Surface energy balance and actual evapotranspiration of the transboundary Indus Basin estimated from satellite measurements and the ETLook model *Water Resour. Res.* **48** W11512
- Bastiaanssen W G M, van der Wal T and Visser T N M 1996 Diagnosis of regional evaporation by remote sensing to support irrigation performance assessment *Irrig. Drain. Syst.* **10** 1–23
- Bhatti M T, Anwar A A and Shah M A A 2019 Revisiting telemetry in Pakistan's Indus basin irrigation system *Water* **11** 2315
- Bierkens M F P and Wada Y 2019 Non-renewable groundwater use and groundwater depletion: a review *Environ. Res. Lett.* **14**
- Briscoe J and Qamar U 2005 Pakistan's water economy: running dry World Bank Washington DC (available at: <http://documents1.worldbank.org/curated/en/989891468059352743/pdf/443750PUB0PK0W1Box0327398B01PUBLIC1.pdf>) (Accessed July 2020)
- Burt C M, Clemmens A J, Strelkoff T S, Solomon K H, Bliessner R D, Hardy L A, Howell T A and Eisenhauer D E 1997 Irrigation performance measures: efficiency and uniformity *J. Irrig. Drain. Eng.* **123** 423–42
- Ceccato P, Flasse S and Gregoire J M 2002 Designing a spectral index to estimate vegetation water content from remote sensing data-Part 2. Validation and applications *Remote Sens. Environ.* **82** 198–207
- Cheema M J M 2012 Understanding water resources conditions in data scarce river basins using intelligent pixel information: transboundary Indus Basin, Technische Universiteit Delft (available at: <http://resolver.tudelft.nl/uuid:7b569411-9934-4b23-b631-36a58f60363f>) (Accessed July 2020)
- Cheema M J M, Ahmad M D, Khaliq T, Liakat M U, Khan M M and Amin H 2020 Quantification of land use changes in complex cropping of irrigated Indus Basin, Pakistan using MODIS vegetation time series data *Pak. J. Agric. Sci.* **57** 489–498
- Cheema M J M and Bastiaanssen W G M 2012 Local calibration of remotely sensed rainfall from the TRMM satellite for different periods and spatial scales in the Indus Basin *Int. J. Remote Sens.* **33** 2603–27
- Cook E R, Palmer J G, Ahmed M, Woodhouse C A, Fenwick P, Zafar M U, Wahab M and Khan N 2013 Five centuries of Upper Indus River flow from tree rings *J. Hydrol.* **486** 365–75
- Donohue R J, Mcvicar T R and Roderick M L 2010 Assessing the ability of potential evaporation formulations to capture the dynamics in evaporative demand within a changing climate *J. Hydrol.* **386** 186–97
- Emelyanova I V, Mcvicar T R, Van Niel T G, Li L T and van Dijk A J J M 2012 On blending Landsat–MODIS surface reflectances in two landscapes with contrasting spectral, spatial and temporal dynamics WIRADA project 3.4: Technical report p 72 (Australia: CSIRO Water for a Healthy Country Flagship) (available at: <https://publications.csiro.au/rpr/pub?list=SEA&pid=csiro:EP128838>) (Accessed August 2020)
- FAO 2012 Irrigation in Southern and Eastern Asia in figures: AQUASTAT Survey—2011 p 512 (Rome: Food and Agriculture Organization of The United Nations) (available at: www.fao.org/3/i2809e/i2809e.pdf) (Accessed July 2020)
- FAO 2019 AQUASTAT—FAO's Global Information System on Water and Agriculture Food and Agriculture Organization of the United Nations Rome (available at: www.fao.org/aquastat/en/data-analysis/irrig-water-use/irrig-water-withdrawal/)
- Gleeson T and Wada Y 2013 Assessing regional groundwater stress for nations using multiple data sources with the groundwater footprint *Environ. Res. Lett.* **8**
- Glenn E P, Nagler P L and Huete A R 2010 Vegetation index methods for estimating evapotranspiration by remote sensing *Surv. Geophys.* **31** 531–55
- Glenn E P, Neale C M U, Hunsaker D J and Nagler P L 2011 Vegetation index-based crop coefficients to estimate evapotranspiration by remote sensing in agricultural and natural ecosystems *Hydrol. Process.* **25** 4050–62
- GOP 1991 Apportionment of waters of Indus River system between the provinces of Pakistan Government of Pakistan (available at: <http://mowr.gov.pk/wp-content/uploads/2018/05/APPORTIONMENT-OF-THE-WATERS-OF-THE-INDUS-RIVER-SYSTEM-1991.pdf>) (Accessed July 2020)
- Gorelick N, Hancher M, Dixon M, Ilyushchenko S, Thau D and Moore R 2017 Google Earth Engine: planetary-scale geospatial analysis for everyone *Remote Sens. Environ.* **202** 18–27
- Guerschman J P, Van Dijk A J J M, Mattersdorf G, Beringer J, Hutley L B, Leuning R, Pipunic R C and Sherman B S 2009 Scaling of potential evapotranspiration with MODIS data reproduces flux observations and catchment water balance observations across Australia *J. Hydrol.* **369** 107–19
- Hargreaves G H 1974 Estimation of potential and crop evapotranspiration *Trans. ASAE* **17** 701–4
- Hassan D, Burian S J, Bano R, Ahmed W, Arfan M, Rais M N, Rafique A and Ansari K 2019 An assessment of the Pakistan Water Apportionment Accord of 1991 *Resources* **8**
- Hintze J L and Nelson R D 1998 Violin plots: a box plot-density trace synergism *Am. Stat.* **52** 181–4
- Hirsch R M, Slack J R and Smith R A 1982 Techniques of trend analysis for monthly water-quality data *Water Resour. Res.* **18** 107–21
- Hobbins M, Wood A, Streubel D and Werner K 2012 What drives the variability of evaporative demand across the conterminous United States? *J. Hydrometeorol.* **13** 1195–214
- Huete A, Didan K, Miura T, Rodriguez E P, Gao X and Ferreira L G 2002 Overview of the radiometric and biophysical performance of the MODIS vegetation indices *Remote Sens. Environ.* **83** 195–213
- Iqbal N, Hossain F, Lee H and Akhter G 2017 Integrated groundwater resource management in Indus Basin using satellite gravimetry and physical modeling tools *Environ. Monit. Assess.* **189** 128
- IRSA 2020 IRSA flow data from from 1976–77–2019–20 (Pakistan: Indus River System Authority)
- Karimi P, Bongani B, Blatchford M and de Fraiture C 2019 Global satellite-based ET products for the local level irrigation management: an application of irrigation performance assessment in the sugarbelt of Swaziland *Remote Sens.* **11**
- Karimi P, Molden D, Bastiaanssen W and Cai X L (eds) 2012 *Water Accounting to Assess Use and Productivity of Water:*

- Evolution of a Concept and New Frontiers* (Cheltenham: Edward Elgar) pp 76–88
- Khan H F, Yang Y C E, Ringler C, Wi S, Cheema M J M and Basharat M 2017 Guiding groundwater policy in the Indus Basin of Pakistan using a physically based groundwater model *J. Water Resour. Plan. Manage.* **143**
- Kirby J M and Ahmad M D 2016 Time-series (1980–2012) crop areas and production in the districts and canal commands of Pakistan p 21 (available at: <https://publications.csiro.au/publications/#publication/PIcsiro:EP163815>) (Accessed July 2020)
- Kirby J M, Ahmad M-U-D, Mainuddin M, Khaliq T and Cheema M J M 2017 Agricultural production, water use and food availability in Pakistan: historical trends, and projections to 2050 *Agric. Water Manage.* **179** 34–46
- Kustas W and Anderson M 2009 Advances in thermal infrared remote sensing for land surface modeling *Agric. For. Meteorol.* **149** 2071–81
- Liaquat U W, Choi M and Awan U K 2015 Spatio-temporal distribution of actual evapotranspiration in the Indus Basin irrigation system *Hydrol. Process.* **29** 2613–27
- Moran M S 1994 Irrigation management in Arizona using satellites and airplanes *Irrig. Sci.* **15** 35–44
- Ospina R and Marmolejo-Ramos F 2019 Performance of some estimators of relative variability *Front. Appl. Math. Stat.* **5** 43
- Paca V H D M, Espinoza-Davalos G E, Hessels T M, Moreira D M, Comair G F and Bastiaanssen W G M 2019 The spatial variability of actual evapotranspiration across the Amazon River Basin based on remote sensing products validated with flux towers *Ecol. Process.* **8** 6
- Peña Arancibia J L and Ahmad M D (2020), CMRSET (CSIRO MODIS ReScaled EvapoTranspiration) monthly actual evapotranspiration (ETa) estimates at 500 m resolution for the canal commands in the Indus Basin Irrigated System (IBIS) in Pakistan from March 2000 to December 2018. v1, CSIRO Data Collection (<https://doi.org/10.25919/18h2-vf51>)
- Peña-Arancibia J L, Ahmad M D, Kirby J M and Cheema M J M 2020a Remotely sensed time-series (2000–2018) estimation of evapotranspiration in the Indus Basin: implementation, evaluation and analysis p 34 (Australia: CSIRO) (available at: <https://publications.csiro.au/publications/#publication/PIcsiro:EP20787>) (Accessed July 2020)
- Peña-Arancibia J L, Mainuddin M, Ahmad M D, Hodgson G, Ibn Murad K F, Ticehurst C, Maniruzzaman M, Golam Mahboob M and Kirby J M 2020b Groundwater use and rapid irrigation expansion in a changing climate: hydrological drivers in one of the world's food bowls *J. Hydrol.* **581** 124300
- Qureshi A S, Ahmed Z and Krupnik T J 2014 Groundwater management in Bangladesh: an analysis of problems and opportunities (Bangladesh: CIMMYT) (available at: <https://repository.cimmyt.org/bitstream/handle/10883/4273/56862.pdf>) (Accessed July 2020)
- Qureshi A S and Barrett-Lennard E G (eds) 1998 *Saline Agriculture for Irrigated Land in Pakistan: A Handbook* (Canberra: Australian Centre for International Agricultural Research)
- Rodell M *et al* 2004 The global land data assimilation system *Bull. Am. Meteorol. Soc.* **85** 381–394
- Sen P K 1968 Estimates of regression coefficient based on Kendall's Tau *J. Am. Stat. Assoc.* **63** 1379
- Shah M A A, Anwar A A, Bell A R and Ul-Haq Z 2016 Equity in a tertiary canal of the Indus Basin irrigation system (IBIS) *Agric. Water Manage.* **178** 201–14
- Siddiqi A, Wescoat J L and Muhammad A 2018 Socio-hydrological assessment of water security in canal irrigation systems: a conjoint quantitative analysis of equity and reliability *Water Secur.* **4–5** 44–45
- Simons G, Bastiaanssen W G M, Cheema M J M, Ahmad B and Immerzeel W W 2020 A novel method to quantify consumed fractions and non-consumptive use of irrigation water: application to the Indus Basin irrigation system of Pakistan *Agric. Water Manage.* **236** 106174
- Simons G, Bastiaanssen W, Ngo L A, Hain C R, Anderson M and Senay G 2016 Integrating global satellite-derived data products as a pre-analysis for hydrological modelling studies: a case study for the Red River Basin *Remote Sens.* **8**
- Stewart J P, Podger G M, Ahmad M D, Shah M A, Bodla H, Khero Z and Rana M K I 2018 Indus River System Model (IRSM)—a planning tool to explore water management options in Pakistan: model conceptualisation, configuration and calibration p 155 (Australia: CSIRO) (available at: <https://publications.csiro.au/rpr/download?pid=csiro:EP186945&dsid=DS7>) (Accessed July 2020)
- UN 1960 The Indus Water Treaty 1960 between the Government of India, the Government of Pakistan and the International Bank for Reconstruction and Development p 85 (available at: <https://treaties.un.org/doc/Publication/UNTs/Volume%20419/volume-419-I-6032-English.pdf>) (Accessed July 2020)
- Usman M, Liedl R and Awan U K 2015 Spatio-temporal estimation of consumptive water use for assessment of irrigation system performance and management of water resources in irrigated Indus Basin, Pakistan *J. Hydrol.* **525** 26–41
- Vermote E and Wolfe R 2015 MOD09GA MODIS/Terra surface reflectance daily L2G global 1km and 500m SIN Grid V006 [Data set] (<https://doi.org/10.5067/MODIS/MOD09GA.006>)
- Wada Y and Bierkens M F P 2014 Sustainability of global water use: past reconstruction and future projections *Environ. Res. Lett.* **9**
- Wada Y, van Beek L P H and Bierkens M F P 2012 Nonsustainable groundwater sustaining irrigation: a global assessment *Water Resour. Res.* **48** W00L06
- Watto M A and Muger A W 2016 Groundwater depletion in the Indus Plains of Pakistan: imperatives, repercussions and management issues *Int. J. River Basin Manage.* **14** 447–58
- Weerasinghe I, Bastiaanssen W, Mul M, Jia L and van Griensven A 2020 Can we trust remote sensing evapotranspiration products over Africa? *Hydrol. Earth Syst. Sci.* **24** 1565–86
- Young W J, Anwar A, Bhatti T, Borgomeo E, Davies III S, Gilmont W R G, Leb M, Lytton C, Makin L and Saeed I B 2019 Pakistan: getting more from water. Water security diagnostic p 163 (Washington, DC: World Bank) (available at: <https://documents.worldbank.org/en/publication/documents-reports/documentdetail/251191548275645649/pakistan-getting-more-from-water>) (Accessed October 2020)
- Zhang Y Q, Kong D D, Gan R, Chiew F H S, Mcvicar T R, Zhang Q and Yang Y T 2019 Coupled estimation of 500 m and 8-day resolution global evapotranspiration and gross primary production in 2002–2017 *Remote Sens. Environ.* **222** 165–82
- Zhou J, Jia L and Menenti M 2015 Reconstruction of global MODIS NDVI time series: performance of harmonic analysis of time series (HANTS) *Remote Sens. Environ.* **163** 217–28